



# UL PRIMER

## FLOOR PREPARATION

13 June 2017

### DESCRIPTION

UL Primer is a high performance one component primer for use on porous substrates. Polymer modified formula, designed for use with Bostik's Floor Levelling range

### YOUR SMART ADVANTAGES

- Fast drying and rapid tack allows for early application of leveling compound.
- Will not re-emulsify in water when dry.
- Easily diluted; 2 parts water 1 part primer
- Economical, high coverage rate.
- High bond strength.

### USES

- Primer for use with Bostik range of floor leveling products
- For porous substrates

### PRODUCT CHARACTERISTICS

Colour/s	White
Flammability	Non Flammable

### MIXING

Bostik UL-Primer is supplied in a concentrate form and should be diluted 2 parts water to 1 part UL-Primer.

### APPLICATION

#### Surface Preparation

- Ensure the concrete substrate is clean and free from oil, grease, sealers, curing compounds, paints, polymer coatings, dust or other foreign (bond breaking) matter.
- Excess bitumen, adhesive or laitance should be removed by light scabbling or mechanical

captive shot blasting or grinding, followed by vacuuming to remove debris and dust.

- Apply Bostik UL-Primer to the prepared substrate using a brush, broom or roller in accordance with the relevant Technical Data Sheet
- Allow primer to reach a tacky consistency. Approximate drying times for the tackiness is 40-60 minutes at 50% RH and 25°C
- Extremely porous substrates such as weather damaged slabs, aerated lightweight concrete etc, may require a second coat of primer to avoid pinholes or bubbles in the levelling compound. If a second coat is required:
  - Apply second coat of primer ensuring any ponded primer is brushed out to allow for even drying. Ensure tackiness is reached prior to application of flooring compound.

### COVERAGE

1 litre of Bostik UL-Primer diluted with 2 litres of water will cover approximately 8-10m<sup>2</sup> per litre per coat, depending upon the porosity of the substrate. Do not add more than 2 parts of water.

### STORAGE AND SHELF LIFE

Bostik UL-Primer has a shelf life of approximately 12 months.

### ITEMS

Sap Code	Product	Size	APN Number
30608708	UL PRIMER	5L	9310492200897

## BOSTIK UL PRIMER

### PRECAUTIONS IN USE

Complete details on each of the products mentioned are available on the product Safety Data Sheets. To ensure no harm is caused to persons using Bostik products, it is recommended that all concerned read the appropriate Safety Data Sheets. Visit [www.bostik.com/au](http://www.bostik.com/au) for copies.

**For emergency information contact the Poisons Information Centre, phone 131 126 or the Emergency Response Service, phone 1800 033 111.**



This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Australian Consumer Law (ACL). Sale of the product by Bostik is subject to the Bostik Australia Proprietary Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit [www.bostik.com/au](http://www.bostik.com/au)